

Alcatel-Lucent 3HE00028CA Datasheet



Alcatel-Lucent 3HE00028CA SFP-GIGE-LX-LC ROHS 6/6 DDM Optical Transceiver

3HE00028CA

Alcatel-Lucent 3HE00028CA SFP-GIGE-LX-LC ROHS 6/6 DDM Optical Transceiver

This Alcatel-Lucent 3HE00028CA SFP transceiver provides 1000Base-LX throughput up to 10km over single-mode fiber (SMF) using a wavelength of 1310nm via an LC connector. This easy to install, hot swappable transceiver has been programmed, uniquely serialized and data-traffic and application tested to ensure that it will initialize and perform identically. Digital optical monitoring (DOM) support is also present to allow access to real-time operating parameters. This transceiver is Trade Agreements Act (TAA) compliant.

Specifications

- Manufacturer: Alcatel-Lucent
- Part Number: 3HE00028CA
- Form Factor: SFP
- Data Rate: 1.25Gb/s
- Wavelength: 1310 nm
- Fiber Type: SMF
- Max Distance: 10 km
- Optical Components: FP/PIN
- Transmitter Power: -9 ~ -3 dBm
- Extinction ratio: > 9 dB
- Receiver Sensitivity: < -22 dBm
- Receiver Overload: > 0 dBm

- Connector: LC Duplex
- Digital Diagnostic Monitoring: Yes
- Operating Temperature: 0°C to 70°C
- Storage Temperature: -40°C to 85°C
- Weight: 0.025 kg
- Application: Gigabit Fibre Channel, Gigabit Ethernet
- Compliance
 - IEC/EN 61000-4-2, IEC-60825
 - FDA 21CFR 1040.10 and 1040.11
 - RoHS

[Buy Now](#)