

Intel AFBR-703SDZ-IN2 Datasheet



Intel AFBR-703SDZ-IN2 SFP Transceiver 2-Rate 1G/10G SFP+ SR

AFBR-703SDZ-IN2

Intel AFBR-703SDZ-IN2 SFP Transceiver 2-Rate 1G/10G SFP+ SR

Features

- Operating Data Rate up to 10.3Gbps
- Single 3.3V Power Supply and TTL Logic Interface
- Hot Pluggable
- 850nm VCSEL Transmitter
- Reach:
 - OM1 (62.5/125micron) 33m
 - OM2 (50/125micron 400 MHz*km) 82m
 - OM3 (50/125micron 2000 MHz*km) 300m
 - OM4 (50/125micron 4700) 300m
- Operating Case Temperature
 - Standard: 0°C~+70°C
 - Industrial: -40°C~+85°C
- Compliant with MSA
- Compliant with IEEE 802.3ae 10GBASE-SR
- Digital Diagnostic Monitor Interface
- Compliant with SFF-8472
- RoHS 6 Compliant

Specifications

- Form Factor: SFP+
- TX Wavelength: 850nm
- Reach: 300m
- Cable Type: MMF
- Rate Category: 10GBase
- Interface Type: SR
- DDM: Yes
- Connector Type: Dual-LC
- Temperature: Commercial
- Power Budget: 5.1dB
- TX Power Min/Max: -6.00 t-1.00
- RX Power Min/Max: -11.1 t-1.00

[Buy Now](#)