

Cisco AIR-ANT2524DG-R Datasheet



Cisco AIR-ANT2524DG-R Aironet Gray Dual-band Dipole Antenna

AIR-ANT2524DG-R

Cisco AIR-ANT2524DG-R Aironet Gray Dual-band Dipole Antenna

This describes the Cisco Aironet high-performance, dual-band dipole antenna, and provides specifications and mounting instructions. The antenna operates in both the 2.4 GHz and 5 GHz frequency bands, and is designed for use with Cisco Aironet 2.4 GHz and 5 GHz radio products with dual-band reverse-polarity TNC (RP-TNC) antenna ports. The antenna has a nominal gain of 2 dBi in the 2.4 GHz frequency band and 4 dBi in the 5 GHz frequency band. The AIR-ANT2524Dx-R antennas covered in this document are electrically the same but differ physically by the color of the radome, which is specified by the product part number shown in Table 1. The AIR-ANT2524DW-RS antenna includes self-identifying circuitry.

Antenna Radome Colors

- AIR-ANT2524DB-R: Black
- AIR-ANT2524DG-R: Gray
- AIR-ANT2524DW-R: White

Specifications

- Antenna type: Dual-band dipole
- Operating frequency range
 - 2400 to 2500 MHz

- 5150 to 5850 MHz
- Nominal input impedance: 50 Ohms
- VSWR: Less than 2:1
- Peak Gain @ 2.4 GHz: 2 dBi
- Peak Gain @ 5 GHz: 4 dBi
- Elevation plane 3dB beamwidth @2.4 GHz: 63 degrees
- Elevation plane 3dB beamwidth @ 5 GHz: 39 degrees
- Connector type: RP-TNC plug
- Antenna length: 6.63 in. (168.5 mm)
- Antenna width: 0.83 in (21 mm)
- Radome length: 4.88 in. (124 mm)
- Weight: 1.3 oz
- Operating temperature: -4° to 140°F(-20°C to 60°C)
- Storage temperature: -40°F to 185°F(-40°C to 85°C)
- Environment: Indoor, office

System Requirements

This antenna is designed for use with Cisco Aironet access points that support simultaneous operation in the 2.4 GHz band and the 5 GHz band and that have dual-band antenna ports, labeled in orange text.

The Self Identifying Antenna model AIR-ANT2524DW-RS= is supported only on Cisco Catalyst 9800 Series Wireless Controllers running an IOS-XE 17.4.1 release or a later release. This antenna model is not supported on Cisco AireOS Wireless Controllers.

Features

The antenna has an articulated base that can be rotated 360 degrees at the connection point and from 0 to 90 degrees at its joint.

The AIR-ANT2524DW-RS antenna includes circuitry to enable self identification of the antenna by the Cisco Catalyst 91xx Series access points. The self identifying function is indicated by a purple band on the antenna. Ensure this antenna is connected to Port A on the AP, which is also designated by purple text around the RP-TNC connector. This antenna has a built-in EEPROM that can be read by the AP to automatically configure the antenna type and gain in the

Wireless LAN Controller.

Installing the Antenna

Caution: The AIR-ANT2524Dx-R series of antennas are dual-band antennas, meaning that they operate in both the 2.4 GHz and 5 GHz frequency bands. The AIR-ANT2524Dx-R series antennas have an orange ID band on them to indicate their dual-band functionality. Connect these antennas only to dual-band antenna ports, which are identified with orange text on Cisco Aironet access points. Using these antennas on Cisco Aironet access points that employ single-band antennas might result in lower performance.

To install the antenna:

1. Verify that the connector to which you are connecting the antenna is a dual-band antenna port, identified by orange text on the access point.
2. Align the antenna connector with the RP-TNC connector on the access point.
3. Engage the antenna connector threads with the RP-TNC connector on the access point.
4. Hand tighten the antenna to the port using the metal knurled ring only. Warning: Do not use the plastic body to tighten. This may damage the antenna.
5. Adjust the antenna articulating joint to the desired position.

[Buy Now](#)