

Cisco AIR-CAP1702I-S-K9 Datasheet



Cisco AIR-CAP1702I-S-K9 Aironet 1700 Series AP, 802.11a/g/n/ac Ctrlr-based AP, Int Ant, S Reg Domain, 3x3 MIMO, 867Mbps

AIR-CAP1702I-S-K9

Cisco AIR-CAP1702I-S-K9 Aironet 1700 Series AP, 802.11a/g/n/ac Ctrlr-based AP, Int Ant, S Reg Domain, 3x3 MIMO, 867Mbps

The Cisco Aironet 1700 Series is a 802.11ac-enabled Aironet Series Access Point that deliver high-performance, comprehensive mobility experiences.

The AIR-CAP1702I-S-K9 offers

- Entry-level access points for small to midsize organizations
- The Cisco AP 1700 offers an attractive price and performance for migrating to 802.11ac
- 802.11ac Wave 1 support with 3x3 multiple input, multiple output (MIMO) equalization
- Cisco CleanAir Express Spectrum Intelligence across 20-, 40-, and 80-MHz-wide channels
- Optimized Roaming intelligently decides proper access points as people move

Specifications

- Product Code: AIR-CAP1702I-S-K9
- WiFi Standards: 802.11a/b/g/n/ac
- Ideal For: Small and Midsize enterprises
- Max Data Rate 5GHz: 867 Mbps
- MIMO Radio Design: Spatial Streams: 3 x 3:2

- Client count/ClientLink client count: 200/-
- Controller Available: Yes
- Power
 - 802.3af PoE
 - 802.3at PoE+
 - Enhanced PoE
 - Power injectors
 - Local power supply
- Antenna: Internal Antenna
- Regulatory Domain
 - S (S regulatory domain):
 - 2.412 to 2.472 GHz; 13 channels
 - 5.180 to 5.320 GHz; 8 channels
 - 5.500 to 5.700 GHz; 11 channels
 - 5.745 to 5.825 GHz; 5 channels
- Dimensions (W x L x H): 22.1 x 22.1 x 5.1 cm (without mounting bracket)
- Package Weight: 2.0 Kg

For more information of this Cisco AIR-CAP1702I-S-K9, please visit Cisco website:

<https://www.cisco.com/c/en/us/products/collateral/wireless/aironet-1700-series/datasheet-c78-732347.html>

[Buy Now](#)