

# Cisco AIR-CAP2702I-H-K9 Datasheet



Cisco AIR-CAP2702I-H-K9 Aironet 2700 AP, 3\*4 MIMO technology, IEEE 802.11a/g/n/ac, 2.4GHz-5GHz, Control Base, Internal antennas, H Reg Domain

AIR-CAP2702I-H-K9

Cisco AIR-CAP2702I-H-K9 Aironet 2700 AP, 3\*4 MIMO technology, IEEE 802.11a/g/n/ac, 2.4GHz-5GHz, Control Base, Internal antennas, H Reg Domain

Based on the Cisco Aironet heritage of RF excellence, the 2700 Series utilizes a Purpose-built innovative chipset to provide a high density experience for enterprise network. 3 x 4 MIMO (multiple-input multiple-output) technology with three-spatial-stream offers a greater coverage for more reliability and capacity than competing access points. AIR-CAP2702I-H-K9 is one of the 2700 series AP, needing wireless controller, providing internal antenna and H regulatory domain.

## Specifications

- Product Code: AIR-CAP2702I-H-K9
- WiFi Standards: 802.11a/b/g/n/ac
- Ideal For: Midsize or large enterprises that require advanced features
- Max Data Rate 5GHz: 1.3 Gbps
- MIMO Radio Design: Spatial Streams: 3 x 4:3
- Client count/ClientLink client count: 200/128
- Controller Available: Yes
- Power
  - 802.3at PoE+
  - Enhanced PoE
  - Cisco AP2700 power injectors

- Cisco AP2700 local power supply
- Note: If 802.3af PoE is the source of power, the access point will dynamically shift from 3x4 to 3x3 and come up under PoE.
- Antenna: Internal Antenna
- Regulatory Domain
  - H (H regulatory domain):
  - 2.412 to 2.472 GHz; 13 channels
  - 5.150 to 5.350 GHz; 8 channels
  - 5.745 to 5.825 GHz; 5 channels
- Dimensions (W x L x H): 22.1 x 22.1 x 5.1 cm (without mounting bracket)
- Weight: 1.0 Kg

For more information of this Cisco AIR-CAP2702I-H-K9, please visit Cisco website:

<https://www.cisco.com/c/en/us/products/collateral/wireless/aironet-2700-series-access-point/datasheet-c78-730593.html>

[Buy Now](#)