

Cisco AIR-CAP3602E-A-K9 Datasheet



Cisco AIR-CAP3602E-A-K9 3600 Dual Band 802.11n Ctrlr-based AP w/CleanAir; 4x4:3SS; Mod; Ext Ant; A Reg Domain
AIR-CAP3602E-A-K9

Cisco AIR-CAP3602E-A-K9 3600 Dual Band 802.11n Ctrlr-based AP w/CleanAir; 4x4:3SS; Mod; Ext Ant; A Reg Domain

Designed to address the wireless connectivity needs of factories, large office and other indoor industrial environment, AIR-CAP3602E-A-K9 is the enterprise class, three-spatial-stream access point with Dual-band, controller-based 802.11a/g/n, external antennas and A regulatory domain. Cisco Aironet 3600 series delivers industry leading performance for secure and reliable wireless connection with up to 450 Mbps or 1.3 Gbps with IEEE802.11ac module over great coverage to ensure the robust mobility experience.

Control-based Cisco Aironet 3600 series access point, a component of the Cisco Unified Wireless Network, enables the capability to support voice, location services, guest access, and advanced security and scales to up to 18,000 access points with full Layer 3 mobility across central or remote locations. Modular architecture enables flexible add-on options, which include Wireless Security Module, IEEE802.11ac module or the Cisco Universal Small Cell 5310 Module.

Specifications

- Brand Name: Cisco
- Product Code: AIR-CAP3602E-A-K9
- RAM: 256 MB
- Wireless Type: 802.11G, 802.11n
- Item Weight: 2.5 pounds
- Product Dimensions: 8.7 x 8.7 x 2.1 inches

- Item Dimensions L x W x H: 8.7 x 8.7 x 2.13 inches
- Flash Memory Size: 32

Frequency Band and 20-MHz Operating Channels

- A (A regulatory domain):
- 2.412 to 2.462 GHz; 11 channels
- 5.180 to 5.320 GHz; 8 channels
- 5.500 to 5.700 GHz, 8 channels (excludes 5.600 to 5.640 GHz)
- 5.745 to 5.825 GHz; 5 channels

For more information of this Cisco AIR-CAP3602E-A-K9, please visit Cisco website:

https://www.cisco.com/c/en/us/products/collateral/wireless/aironet-3600-series/data_sheet_c78-686782.html

[Buy Now](#)