

Cisco AIR-PWR-B Datasheet



Cisco AIR-PWR-B 3600 Series Local Power Supply

AIR-PWR-B

The single-port Cisco Aironet Power Injector AIR-PWR-B provides 802.3af power and data signal, sending both to the Cisco Aironet Access Point.

Specifications

- Dimensions: 8 x 7.5 x 2 inches
- Cooling Type: Air
- Input Voltage Range: 100 V AC to 240 V AC
- Output Voltage: 48 V DC
- Maximum Output Current: 380 mA

Compatibility

Cisco Aironet 1041 Controller-based, Cisco Aironet 1041 Standalone, Cisco Aironet 1042 Controller-based, Cisco Aironet 1042 Standalone, Cisco Aironet 1130AG, Cisco Aironet 1131AG, Cisco Aironet 1131G, Cisco Aironet 1141 Standalone, Cisco Aironet 1142 Controller-based, Cisco Aironet 1142 Standalone, Cisco Aironet 1242AG, Cisco Aironet 1242G, Cisco Aironet 1260 Series Access Point (Controller-based), Cisco Aironet 1310 Outdoor Access Point/Bridge, Cisco Aironet 3501e, Cisco Aironet 3502e, Cisco Aironet 3502i, Cisco Aironet 3502P, Cisco Aironet 3602E, Cisco Aironet 3602I, Cisco Aironet 3602p Controller-Based Access Points

[Buy Now](#)