

Adaptec ASR-5805 Datasheet



Adaptec ASR-5805 2244300-R 3Gb/s 8-port Internal SAS/SATA RAID Controller with 512MB Cache

ASR-5805

Adaptec ASR-5805 2244300-R 3Gb/s 8-port Internal SAS/SATA RAID Controller with 512MB Cache

8 internal port, low profile, PCI-Express (PCIe) Unified Serial RAID controller with Intelligent Power Management delivers exceptional performance, advanced data protection, and maximum scalability for enterprise-class, high-density server applications

Supported Operating Systems

- Microsoft Windows
- Red Hat Linux
- SUSE Linux
- SCO OpenServer
- UnixWare
- Sun Solaris
- FreeBSD
- VMware ESX

Benefits

- Performance Unified Serial RAID controller supports both SATA and SAS devices. Ideal for bandwidth intensive storage applications; NAS, OLTP servers, web servers, and digital surveillance.

Key Differentiators

- Intelligent Power Management

Customer Needs

- High I/O transaction and high bandwidth processing.

Form Factor

- MD2 Low-Profile

Cache Memory

- 512MB of DDR2 memory

RAID Levels

- RAID levels 0, 1, 1E, 5, 5EE, 6, 10, 50 and 60

Key RAID Features

- Supports 8 direct-attached or up to 256 SATA or SAS disk drives
- using SAS expanders
- RAID levels 0, 1, 1E, 5, 5EE, 6, 10, 50 and 60
- Quick initialization
- Online Capacity Expansion
- Copyback Hot Spare
- Dynamic caching algorithm
- Native Command Queuing (NCQ)
- Background initialization
- Hot-plug drive support
- RAID Level Migration
- Hot spares – global, dedicated, and pooled

- Automatic/manual rebuild of hot spares
- SAF-TE enclosure management
- Configurable stripe size
- S.M.A.R.T. support
- Up to 512TB array sizes
- Multiple arrays per disk drive
- Bad stripe table
- Dynamic sector repair
- Staggered drive spin-up
- Bootable array support
- Optimized Disk Utilization

Bus System Interface Type

- 8-lane PCIe

Internal Connectors

- 2 internal (SFF-8087) Mini SAS

Data Transfer Rate

- 3 Gb/s per port

Package Contents

- Adaptec RAID 5805 Controller
- Additional low profile vented bracket
- Quick Installation Guide (English/French/German/Italian/Spanish)
- Software and documentation CDs
- Cables: two internal Mini SAS x4 to (4x) SATA fanout cables w/ sideband, 0.5 meter

Management Utilities

- Adaptec Storage Manager™ (ASM)

- Java-based GUI Management Utility
- Remote configuration, monitoring & notification
- ASM OS Support: Windows, Linux, SCO, Solaris, FreeBSD
- Microsoft VDS Support
- SNMP, SMTP
- Remote firmware updates

ARCCONF

- Command Line Interface
- SMI-S support for VMware

Adaptec BIOS Utility (ACU)

- BIOS level configuration utility
- Flashable BIOS support

Physical Size

- 2.5" H x 6.6" L (64mm x 167mm)

Operating Temperature

- 0°C to 55°C* (with 200 LFM airflow; without battery)
- 0°C to 40°C* (with 200 LFM airflow; with battery)

Note: This Adaptec card contains a powerful RAID processor which requires adequate airflow to operate reliably. Please install this card only into server or PC chassis with recommended airflow (200 LFM).

* Ambient temperature measured 1" away from the RAID processor

Operating Voltage

- 0.45 amp @ 3.3V
- 1 amp @ 12V

Regulatory Certification

- CE, FCC, UL, C-tick, VCCI

Mean Time Before Failure (MTBF)

- 873,402 hours at 40 degree C.

[Buy Now](#)