

# Brocade BR-1860-2F00 Datasheet



Brocade BR-1860-2F00 Dual port 16Gbps Fibre Channel HBA, SWL SFP+ included

BR-1860-2F00

## Specifications

- Brand Name: Brocade
- Manufacturer P/N: BR-1860-2F00
  
- Number of Ports/Channels: 2 ports
- Protocols: FC/DCB/FCoE/iSCSI
- Data Transfer Rate: 16/8/4/2 Gbps
- Bus Type: PCI Express 2.0 x8

## Operating System Support

- VMware ESX 3.5
- VMware ESX/ESXi 4.0 , U1, U2
- VMware ESX/ESXi 4.1 , U1
- VMware ESXi 5.0
- VMware ESXi 5.1
- VMware ESXi 5.5
- Microsoft Hyper-V Server 2008
- Citrix XenServer 6.1
- Oracle VM 3.1.1 (or later)

- Windows Server 2008 SP1/SP2 (32 bit)
- Windows Server 2008 SP1/SP2/R2 (64 bit)
- Windows 7 Enterprise/Windows 7 Enterprise SP1 (32 bit)
- Windows 7 Enterprise/Windows 7 Enterprise SP1 (64 bit)
- Windows Server Core (32/64-bit)
- Windows PE (32 bit)
- Windows PE (64 bit)
- Windows Server 2012 (64 bit)
- Windows Server 2012 R2 (64 bit)
- Red Hat Enterprise Linux 4.6, 4.7, 4.8, 4.9 (32 bit)
- Red Hat Enterprise Linux 4.6, 4.7, 4.8, 4.9 (64 bit)
- Xen for Red Hat Enterprise Linux 5
- Red Hat Enterprise Linux 5.2, 5.3, 5.4, 5.5, 5.6 (32 bit)
- Red Hat Enterprise Linux 5.2, 5.3, 5.4, 5.5, 5.6 (64 bit)
- Red Hat Enterprise Linux 5.2, 5.3 (IA64 bit)
- Red Hat Enterprise Linux 5.7, 5.8, 5.9 (32 bit)
- Red Hat Enterprise Linux 5.7, 5.8, 5.9 (64 bit)
- Red Hat Enterprise Linux 6.0, 6.1, 6.2, 6.3, 6.4 (32 bit)
- Red Hat Enterprise Linux 6.0, 6.1, 6.2, 6.3, 6.4 (64 bit)
- Xen for SUSE Linux Enterprise Server 10
- SUSE Linux Enterprise Server 10 SP1, SP2, SP3, SP4 (32 bit)
- SUSE Linux Enterprise Server 10 SP1, SP2, SP3, SP4 (64 bit)
- SUSE Linux Enterprise Server 10.3, 10.4 (32 bit)
- SUSE Linux Enterprise Server 10.3, 10.4 (64 bit)
- Xen for SUSE Linux Enterprise Server 11 (32/64 bit)
- KVM for SUSE Linux Enterprise Server 11 (32/64 bit)
- SUSE Linux Enterprise Server 11, SP1 (32 bit)
- SUSE Linux Enterprise Server 11, SP1 (64 bit)
- SUSE Linux Enterprise Server 11.1, 11.2, 11.3 (32 bit)
- SUSE Linux Enterprise Server 11.1, 11.2, 11.3 (64 bit)
- Solaris 10 x86 (32 bit)
- Solaris 10 x86 (64 bit)
- Solaris 10 SPARC (64 bit)
- Solaris 11 x86 (64 bit)
- Solaris 11 SPARC (64 bit)
- VMware ESX 4.1 (64 bit)
- VMware ESX 5.0, 5.1 (64 bit)

- Oracle Enterprise Linux 5.7, 5.8 (32 bit)
- Oracle Enterprise Linux 5.7, 5.8 (64 bit)
- Oracle Enterprise Linux 6.1, 6.2 (32 bit)
- Oracle Enterprise Linux 6.1, 6.2 (64 bit)

## Media Support

- Brocade 8Gb SFP+, SWL (XBR-000147, XBR-000163)
- Brocade 8Gb SFP+, LWL, 10Km (XBR-000153)
- Brocade 16Gb SFP+, SWL (XBR-000192)
- Brocade 16Gb SFP+, LWL 10Km (XBR-000198)

## DataSheet

- BR-1860-2F00 Datasheet

[Buy Now](#)