Cisco CAB-STK-E-1M Datasheet

Cisco Bladeswitch 1M stack cable

CAB-STK-E-1M

The Cisco CAB-STK-E-1M Flex Stack stacking cables connect your Catalyst 2960-X and 2960-XR stackable switches into a single switching unit. They allow you to make easy adds, moves or changes without interruption, minimizing downtime for your business. Additionally, you can use these stacking cables to stack up to eight switches, becoming one master switch. Available in 0.5M, 1 Meter, and 3 Meter lengths.

Features

- Stacking technology allows for a single configuration of up to 8 stacked switches
- Speeds up to 20 Gbps on Cisco Catalyst 2960-S and 2960-SF using C2960S-STACK or 2960S-F-STACK FlexStack Module
- Speeds up to 40 Gbps on Cisco Catalyst 2960-X and 2960-XR using C2960X-STACK FlexStack Plus or C2960X-HYBRID-STK FlexStack extended hybrid module
- Also available in 0.5 Meter, 1 Meter, and 3 Meter lengths

Specifications

- Manuf Part#: CAB-STK-E-1M=
- Part Number: 37-0890-01

- Description: Cisco Bladeswitch 1M stack cable
- Type: Stacking cable
- Connector 1: Stack
- Connector 2: Stack
- Length: 1 meter
- Color: Black
- Conductor Material: Copper

Compatibility

The CAB-STK-E-1M is designed for Cisco Catalyst 2960-24LC-S, 2960-24LT-L, 2960-24PC-L, 2960-24PC-S, 2960-24-S, 2960-24TC, 2960-24TC-L, 2960-24TC-S, 2960-24TT, 2960-48PST-L, 2960-48PST-S, 2960-48T, 2960-48TC, 2960-48TC-L, 2960-48TC-S, 2960-48TT, 2960-48TT-L, 2960-48TT-S, 2960-8TC, 2960-8TC-S, 2960G-24TC, 2960G-48TC, 2960G-8TC, 2960PD-8TT-L, 2960S-24PD-L, 2960S-24PS-L, 2960S-24TD-L, 2960S-24TS-L, 2960S-24TS-S, 2960S-48FPD-L, 2960S-48FPS-L, 2960S-48LPD-L, 2960S-48LPS-L, 2960S-48TD-L, 2960S-48TS-L, 2960S-48TS-S, Blade Switch 3120G for HP, Blade Switch 3120X for HP, Blade Switch 3130G for Dell M1000e with IP Base, Blade Switch 3130X for Dell M1000e with IP Base, Switch Module 3110G for IBM BladeCenter, Switch Module 3110X for IBM BladeCenter

Buy Now