

# Cisco CPAK-100G-PSM4 Datasheet



Cisco CPAK-100G-PSM4 100GBASE PSM4 CPAK Module for SMF

CPAK-100G-PSM4

Cisco CPAK 100GBASE fiber modules for Cisco switches and routers offer a selection of high-density 100-Gbps connectivity solutions. The modules are especially well suited for connections in enterprise and service provider data centers and in service provider edge networks.

The line cards use the Cisco CPAK form factor. They are 20 percent smaller and consume 40 percent less power than C Form-Factor Pluggable 2 (CFP2) modules; they use 70 percent less power than the CFP interface. Cisco CPAK modules give you up to 20 percent greater port density and front-panel bandwidth than competing products.

Choose the model that matches the distance you need to cover, the type of fiber cabling you are using, and the Cisco networking product you are using. Cisco CPAK 100GBASE modules work in the following Cisco networking equipment: ASR 1000 Series Router; ASR 9000 Series Router; CRS-X Carrier Routing System; NCS 2000, 4000, and 6000 Series Routers; the Nexus 7000 and 7700 Series Switches, and the Cisco ONS Transport Platform.

Features and benefits

Cisco CPAK modules combine high density and bandwidth with low power consumption and are interoperable with any IEEE-compliant 100GBASE-LR4 or 100GBASE-SR10 for investment protection and product choice. Some models, including the Cisco CPAK 100GBASE-LR4, use Cisco Complementary Metal-Oxide Semiconductor (CMOS) photonic technology to provide industry-leading optical integration, performance, power savings, and scalability.

#### Cisco CPAK-100G-PSM4 CPAK 100GBASE PSM4 Module

The Cisco CPAK-100G-PSM4 Module supports link lengths of up to 500 meters over Single-Mode Fiber (SMF) with MPO connectors. The 100 Gigabit Ethernet signal is carried over 12-fiber parallel fiber terminated with MPO multifiber connectors.

#### Specifications

- Product Number: CPAK-100G-PSM4
- Description: Cisco 100GBASE PSM4 CPAK Module for SMF
- Connector: 12-fiber MPO/MTP connector
- Wavelength: 1295 to 1325nm
- Cable Type: SMF (12 fibers)
- Cable Distance: 500m
- Transmit Power (dBm):
  - Maximum: +2.0 per lane
  - Minimum: -9.4 per lane
- Receive Power (dBm):

- Maximum: +2.0 per lane
- Minimum: -9.4 per lane
- Transmit and Receive Center Wavelength Range (nm): Four lanes: 1295 to 1325

## Dimensions

- Maximum outer dimensions for the Cisco CPAK-100G-PSM4 module (H x W x D): 11.6 x 34.8 x 101.2 mm (0.46 x 1.37 x 3.98 in).
- The Cisco CPAK modules typically weigh approximately 127 grams (4.48 oz.).

## Environmental conditions and power requirements

- Operating temperature range: 0 to 70° C (32 to 158° F)
- Storage temperature range: -40 to 85° C (-40 to 185° F)
- CPAK-100G-PSM4 power consumption at 70° C: