

D-Link DEM-434XT-DD Datasheet



D-Link DEM-434XT-DD 10GBase-ZR SFP+ Transceiver (SMF, 1550nm, 80km, LC, DOM)

DEM-434XT-DD

D-Link DEM-434XT-DD 10GBase-ZR SFP+ Transceiver (SMF, 1550nm, 80km, LC, DOM)

D-Link DEM-434XT-DD is a high performance and cost-effective SFP+ transceiver module, supporting data-rate of 10.3125Gbps (10GBASE-ZR) or 9.953Gbps (10GBASE-ZW) over single mode optical fiber. This Product is programmed to be compatible with a wide range of D-Link network equipment, such as 10 Gigabit Ethernet (10 GbE) Switches, Routers, Network Interface Cards (NICs) and Media Converters. Additionally, this module also provides a unique enhanced digital diagnostic monitoring interface(DDMI) per SFF-8472, which providing real-time monitoring of the transceiver optics temperature, laser bias current, optical power, received optical power and transceiver optics supply voltage.

Features

- Electrical interface compliant to SFF-8431
- Compliant with SFF-8472
- 10Gb/s serial optical interface compliant to 802.3ae 10GBASE-ZR
- 1550nm EML transmitter, APD receiver
- Built-in digital diagnostic functions
- Single 3.3V power supply
- Metal enclosure, for lower EMI
- ROHS compliant and lead-free

Specifications

- Part Number: DEM-434XT-DD
- Brand: D-Link
- Form Factor: SFP+
- Data Rate: 10Gb/s
- Wavelength: 1550 nm
- Fiber Type: SMF
- Max Distance: 80 km
- Optical Components: EML/APD
- Transmitter Power: 0 ~ 5 dBm
- Extinction ratio: > 7 dB
- Receiver Sensitivity: < -24 dBm
- Receiver Overload: > -7 dBm
- Connector: LC Duplex
- Digital Diagnostic Monitoring: Yes
- Environment
 - Operating: 0°C to 70°C
 - Storage: -40°C to 85°C
- Weight: 0.03 kg
- Application
 - 10GBASE-ZR/10GBASE-ZW Ethernet
 - 10G Fiber Channel
 - 10GbE Data Center Switches and Routers
- Compliance
 - IEC/EN 61000-4-2, IEC-60825
 - FDA 21CFR 1040.10 and 1040.11
 - RoHS

[Buy Now](#)