

D-Link DEM-S2801SR Datasheet



D-Link DEM-S2801SR 25GBASE-SR Multi-Mode 100 m SFP28 Transceiver

DEM-S2801SR

D-Link DEM-S2801SR 25GBASE-SR Multi-Mode 100 m SFP28 Transceiver

D-Link's 25G SFP28 Module series are hot-swappable SFP28 transceivers that are plugged into SFP28 slots on switches and support 25G Ethernet. The transceivers use the Small Form-factor Pluggable 28 format (SFP28) connectors. The D-Link 25G SFP28 Module Series transceivers offer customers a wide variety of 25G Ethernet connectivity options for data centers, enterprise wiring closets, and service provider transport applications.

Hot Pluggable

All D-Link transceivers are hot pluggable. You can connect a transceiver while the system is powered on without causing any issues, and easily swap one for another without having to reboot the switch each time. This permits modules to be added or removed without interrupting the network, facilitating maintenance and greatly reducing downtime.

25G Ethernet speeds

The transceivers support 25G Ethernet, which results in very fast data transmissions of up to 25 Gbit/s. This is 25 times faster than Gigabit Ethernet and enables the switch to handle faster and higher data transmissions, making it very suitable for business needs.

The DEM-S2801SR is a high performance 850nm multimode SFP28 transceiver. Supporting 25 Gigabit speeds on multimode fibre for distances of up to 100m on OM4 or 70m on OM3 fibre.

Specifications

- Transceiver Type: SFP28
- Cable Distance
 - OM3 MMF: 70 m
 - OM4 MMF: 100 m
- Cable Type: Multi-mode 50/125 um OM3, OM4 fiber cable
- Interfaces: Duplex LC connector
- Hot Pluggable: Yes
- Direction: Single direction
- Wavelength: 850 nm

[Buy Now](#)