

# Finisar FTLF1318P3BTL Datasheet



Finisar FTLF1318P3BTL 1000BASE-LX and 1G Fibre Channel (1GFC) 10km Industrial Temperature Gen3 SFP Optical Transceiver

## FTLF1318P3BTL

FTLF1318P3BTL Small Form Factor Pluggable (SFP) transceivers are compatible with the SFP Multi-Sourcing Agreement (MSA). They simultaneously comply with Gigabit Ethernet as specified in IEEE Std 802.3 and 1x Fibre Channel as defined in FC-P1-4 Rev. 8.00. Digital diagnostics functions are available via the 2-wire serial bus specified in the SFP MSA. The optical transceiver is RoHS compliant as described in Application Note AN-2038.

## Features

- Up to 1.25Gb/s bi-directional data links
- Hot-pluggable SFP footprint
- Build-in digital diagnostic functions
- 1310nm Fabry-Perot laser transmitter
- Duplex LC connector
- RoHS compliant
- Up to 10 km on 9/125µm SMF
- Metal enclosure for lower EMI
- Single 3.3V power supply
- Low power dissipation <600mW typical
- Industrial operating temperature range: -40°C to 85°C

## Applications

- 1.25Gb/s 1000Base-LX Ethernet
- 1.06 Gb/s Fibre Channel

## Specifications

- Distance: 10km
- Data Rate (max): 1.25 Gb/s
- Protocol: Optical Gigabit Ethernet Compliant 1x Fibre Channel Compliant Wireless CPRI Compliant
- Low End Case Temperature (°C): -40
- High End Case Temperature (°C): 85
- Diagnostics: Digital
- Transmitter: Fabry-Perot Laser
- Receiver: PIN
- Voltage Supply: 3.3
- Connector: LC
- Wavelength: 1310nm

[Buy Now](#)