

Finisar FTLF1422P1BTL Datasheet



Finisar FTLF1422P1BTL OC-12 LR-1/STM L-4.1 1310nm 40km SFP Optical Transceiver

FTLF1422P1BTL

FTLF1422P1BTL Small Form Factor Pluggable (SFP) transceivers are compatible with the SFP Multi-Sourcing Agreement (MSA). They comply with SONET and SDH standards at OC-12 LR-1/STM L-4.1. Digital diagnostics functions are available via the 2-wire serial bus specified in the SFP MSA. The optical transceiver is RoHS compliant as described in Application Note AN-2038.

Features

- 622 Mb/s bi-directional data links
- Hot-pluggable SFP footprint
- Built-in digital diagnostic functions
- Uncooled DFB 1310nm laser transmitter
- Duplex LC connector
- RoHS compliant
- Metal enclosure, for lower EMI
- Single 3.3V power supply
- Low power dissipation <700mW typical
- Industrial operating temperature range: -40°C to 85°C

Applications

- SONET OC-12 LR-1 / SDH STM L-4.1

Specifications

- Distance: 40km
- Data Rate (max): 622 Mb/s
- Protocol: SONET OC-12 Compliant Wireless CPRI Compliant
- Low End Case Temperature (°C): -40
- High End Case Temperature (°C): 85
- Diagnostics: Digital
- Transmitter: DFB Laser
- Receiver: PIN
- Voltage Supply: 3.3
- Connector: LC
- Wavelength: 1310nm

[Buy Now](#)