

Finisar FTLX1475D3BNL Datasheet



Finisar FTLX1475D3BNL 10G 10km 1310nm Extended Temperature Single Mode Datacom SFP+ Optical Transceiver

FTLX1475D3BNL

Extended Temperature FTLX1475D3BNL 10Gb/s Enhanced Small Form Factor Pluggable SFP+ transceivers are designed for use in 10-Gigabit Ethernet links up to 10km over Single Mode fiber. They are compliant with SFF-8431, SFF-8432 and IEEE 802.3ae 10GBASE-LR/LW and 10G Fibre Channel 1200-SM-LL-L. Digital diagnostics functions are available via a 2-wire serial interface, as specified in SFF-8472. The FTLX1475D3BNL is a “limiting module”, i.e., it employs a limiting receiver. The optical transceiver is RoHS compliant as described in Application Note AN-2038.

Features

- Hot-pluggable SFP+ footprint
- Supports 9.95 to 10.5Gb/s bit rates
- Power dissipation < 1W
- RoHS compliant
- Single 3.3V power supply
- Maximum link length of 10km
- Uncooled 1310nm DFB laser
- Limiting electrical interface receiver
- Duplex LC connector
- Built-in digital diagnostic functions
- Extended temperature range: -5°C to 85°C

Applications

- 10GBASE-LR/LW 10G Ethernet
- 1200-SM-LL-L 10G Fibre Channel

Specifications

- Distance: 10 km
- Data Rate (max): 10.5 Gb/s
- Protocol: 10x Fibre Channel Compliant 10 Gigabit Ethernet Compliant Wireless CPRI Compliant
- Low End Case Temperature (°C): -5
- High End Case Temperature (°C): 80
- Diagnostics: Digital
- Transmitter: DFB Laser
- Receiver: PIN
- Voltage Supply: 3.3
- Connector: LC
- Wavelength: 1310nm

[Buy Now](#)