

Cisco GLC-LX-SM-RGD Datasheet



Cisco GLC-LX-SM-RGD 1000BASE-LX/LH long wavelength; rugged

GLC-LX-SM-RGD

The industry-standard Cisco Small Form-Factor Pluggable (SFP) Gigabit Interface Converter links your switches and routers to the network. The hot-swappable input/output device plugs into a Gigabit Ethernet port or slot. Optical and copper models can be used on a wide variety of Cisco products and intermixed in combinations of 1000BASE-T, 1000BASE-SX, 1000BASE-LX/LH, 1000BASE-EX, 1000BASE-ZX, or 1000BASE-BX10-D/U on a port-by-port basis.

Features and benefits

- Hot swappable to maximize uptime and simplify serviceability
- Flexibility of media and interface choice on a port-by-port basis, so you can “pay as you populate”
- Robust design for enhanced reliability
- Supports Digital Optical Monitoring (DOM) capability

1000BASE-LX/LH SFP for both multimode and single-mode fibers

The 1000BASE-LX/LH SFP, compatible with the IEEE 802.3z 1000BASE-LX standard, operates on standard single-mode fiber-optic link spans of up to 10 km and up to 550 m on any multimode fibers. When used over legacy multimode fiber type, the transmitter should be coupled through a mode conditioning patch cable.

Specifications

- Product Number: GLC-LX-SM-RGD
- Product Description: 1000BASE-LX/LH long wavelength; rugged
- Connector: Dual LC/PC connector
- Wavelength: 1310nm
- Fiber: MMF, SMF

- Operating Distance:
 - 550m (1,804 ft) @ OM1

 - 550m (1,804 ft) @ OM2
 - 10000m (32,821 ft) @ SMF
- Transmit Power Range (dBm): -3 to -9.5
- Receiver Power Range (dBm): -3 to -20
- Wavelength Range (nm): 1270 to 1355
- Dimensions: (H x W x D): 8.5 x 13.4 x 56.5 mm
- Operating temperature range: Industrial temperature range (IND): -40 to 85°C (-40 to 185°F)
- Storage temperature range: -40 to 85°C (-40 to 185°F)

- DOM: Yes

Platform support

- ASA5500 Series Appliances
- ASR 901 and 903 Series Routers
- ASR 1000, 9000, and 9000v Series Routers
- Catalyst Express 500 and Express 520
- Catalyst 2350 and 2360 Series
- Catalyst 2900, 2940, 2950, 2960, 2960-Plus, 2960-C, 2960-S, 2960-SF, 2960-X Series
- Catalyst 2970 and 2975 Series

- Catalyst 3000 and 3100 Blade Switches
- Catalyst 3500XL Series
- Catalyst 3550, 3560, 3560-C, 3560-E, 3560-X Series
- Catalyst 3750-E Series, 3750 Metro, 3750-X Series
- Catalyst 3850 Series
- Catalyst 4500 and 4500-X Series
- Catalyst 4900 Series
- Catalyst 6000 Series
- Catalyst 6800 Series
- Cisco 1941 Series Router
- Cisco 2600, 2800, 2900 Series Router
- Cisco 3200, 3600, 3700 Series Router
- Cisco 4400 Series Router
- Cisco 5700 Series Wireless LAN Controller
- Cisco 6400 Universal Access Router
- Cisco uBR7200 Series
- Cisco 7200, 7300, 7500, and 7600 Series Routers
- Cisco 10000 and uBR 10000 Series Routers
- Cisco 10700 Series Internet Router
- Cisco 12000 Series Router
- Cisco 2000 Connected Grid Router Series
- Cisco 2500 Connected Grid Switch Series
- Cisco IE2000 and IE2000U Series
- Cisco IE3010 Series
- Cisco MDS 9000
- Cisco ME 2400
- Cisco ME 2600X
- Cisco ME 3400
- Cisco ME 3600X and ME 3800X
- Cisco ME 4600 and ME 4900 Series
- Cisco ME 6500 Series
- Cisco MWR 2941 Mobile Wireless Router
- CRS Router Series
- CSS 11500 Series
- Cisco RF Gateway Series
- NAM 2200 Series Appliances
- Nexus 2000, 3000, 4000, 5000, 7000, 9000, 9300, 9500 (modular) Series

[Buy Now](#)