

# Hisense LTD1502-BC Datasheet



Genuine Hisense LTD1502-BC+ 2.5G 1550nm SM 80km SFP Transceiver Module

LTD1502-BC

LTD1502-BC+ - Genuine Hisense LTD1502-BC+ 2.5G 1550nm SM 80km SFP Transceiver Module

## Features

- Type: SFP
- Tx/Rx Wavelength: 1550 nm. / 1550 nm.
- Media Type: Single-Mode Fiber (SMF)
- Optical Budget: 26 dB
- Max. Distance: 80 km
- Data Rate: 100-2.67Gbps
- Temperature: C (0°~70°C)

## Specifications

- Media Type: Single-Mode Fiber (SMF)
- Wavelength: 1550 nm.
- Minimum Optical Budget: 26 dB
- Maximum Distance: 80km
- Supported Data Rate: 100-2.67Gbps
- Supported Applications: Gigabit Ethernet (1.25 Gbps), 100M Ethernet (100Mbps), 2G Fiber Channel (2.125 Gbps), 1G Fiber Channel (1.0625 Gbps), STM-1 (155Mbps), STM-4 (622Mbps), STM-16 (2.488 Gbps), ODU0 (1.244Gbps), ODU1 (2.498Gbps), OTU1 (2.66Gbps), CPRI option 1 (614.4 Mbps), CPRI option 2 (1228.8 Mbps), CPRI option 3

(2.458 Gbps), OBSAI RP3 x 1 (768 Mbps), OBSAI RP3 x 2 (1.536 Gbps)

- DDM/DOM: Support
- Temperature Range: Standard 0°-70°C
- Connectors: Duplex LC

[Buy Now](#)