Mellanox MCP1600-C005 Datasheet



Mellanox MCP1600-C005E26L Passive Copper cable, ETH 100GbE, 100Gb/s, QSFP28, 5m, Black, 26AWG MCP1600-C005E26L

MCP1600-C005

NVIDIA MCP1600-C005E26L Direct Attach Copper Cable Ethernet 100GbE QSFP28 5m Black 26AWG CA-L

100GbE QSFP28 Direct Attach Copper Cable

NVIDIA's direct attach copper (DAC) cables are high speed, cost-effective alternatives to fiber optics in 100Gb/s Ethernet applications.

NVIDIA QSFP28 passive copper cable contains four high-speed copper pairs, each operating at data rates of up to 25GbE. Each QSFP28 connector includes an EEPROM providing product information which can be read by the host system.

NVIDIA's unique quality, passive, copper cable solutions provide power-efficient connectivity for short distance interconnects. They enable higher port bandwidth, density and configurability at a low cost and reduced power requirement in the data centers.

MCP1600-C0xxEyyz cables up to 2m support IEEE 802.3bj CA-25G-N (Cable Assembly No-FEC) with low latency. Cables from 3m to 5m support IEEE 802.3bj CA-25G-L (Cable Assembly Long) with RS-FEC (Reed Solomon Forward Error Correction) enabled(1). For 2.5m and 3m cables there are two versions supporting either CA-25G-N or CA-25G-L.
NVIDIA's unique quality passive copper cable solutions provide power-efficient connectivity for short distance interconnects. They enable higher port bandwidth, density and configurability at a low cost and reduced power requirement in the data centers.
Rigorous cable production testing ensures best out-of-the-box installation experience, performance and durability.
Highlights
• Up to 100GbE data rate

- SFF-8665 compliant QSFP28
- Operating case temperature 0-70C
- Single 3.3V supply voltage
- Bit Error Rate (BER) better than 1E-15
- Hot pluggable
- RoHS compliant
- LSZH (Low Smoke Zero Halogen) jacket
- LF (Lead Free) HF (Halogen Free) PCB
- SFF-8636 compliant I2C management interface