Mellanox MFA1A00-C010 Datasheet



| Mellanox MFA1A00-C010 active fiber cable, ETH 100GbE, 100Gb/s, QSFP, LSZH, 10m |
|--|
| MFA1A00-C010 |

Mellanox 100Gb/s QSFP28 MMF Active Optical Cables

NVIDIA Mellanox MFA1A00-Cxxx are QSFP28 VCSEL-based (Vertical Cavity Surface-Emitting Laser) active optical cables designed for use in 100Gb/s Ethernet systems.

MFA1A00-Cxxx AOC offers high port density and configurability, and a much longer reach than passive copper cables in the data centers. Since the AOC is hot pluggable, it is easy to install and replace.

MFA1A00-Cxxx offers selectable retiming per lane for both its optical transmitters and receivers for the 25Gb/s rate, but the AOC also supports lower bit rates without retiming. The transmitters have programmable input equalizers and input squelch function, while the receivers have programmable output amplitude and pre-emphasis.

| These unique-quality active-fiber cable solutions provide power-efficient connectivity for data center interconnects. |
|---|
| They enable higher port bandwidth, density and configurability at a low cost and reduced power requirement in the |
| data centers. |
| |
| |
| |
| |
| Rigorous production testing ensures the best out-of-the-box installation experience, performance and durability. |
| |
| |
| |
| Highlights |
| |
| |
| • Up to 100Gb/s data rate |
| Programmable Rx output amplitude and pre-emphasis |
| Programmable Tx input equalizer |
| Selectable retiming |
| SFF-8665 compliant QSFP28 port |
| • Single 3.3V power supply |
| • 2.2W power dissipation (typ, each end, with retiming) |
| BER better than 1E-15 |
| Up to 100m length |
| Hot pluggable |
| RoHS compliant |
| SFF-8636 compliant I2C management interface |
| |
| |
| For more specifications of this MFA1A00-C010, please visit below Mellanox website: |
| https://www.mellanox.com/related-docs/prod_cables/PB_MFA1A00-Cxxx_100GbE_QSFP28_MMF_AOC.pdf |
| |
| Buy Now |