OS2-ST-ST-S7M Datasheet



7m (23ft) 9/125 OS2 ST to ST Singlemode Simplex Fiber Optic Patch Cable OS2-ST-ST-S7M

7m (23ft) 9/125 OS2 ST to ST Singlemode Simplex Fiber Optic Patch Cable

The 9/125µm OS2 single mode bend insensitive fiber optic cable is less attenuation when bent or twisted compared with traditional optical fiber cables and this will make the installation and maintenance of the fiber optic cables more efficient. It can also save more space for your high density cabling in data centers, enterprise networks, telecom room, server farms, cloud storage networks, and any places fiber patch cables are needed.

This fiber optic cable is ideal for connecting 1G/10G/25G/40G/100G/400G Ethernet connections. It can transport data for up to 10km at 1310nm, or up to 40km at 1550nm.

Specifications

• Fiber Mode: OS2 9/125µm

• Connector 1: (1) Simplex ST Male

• Connector 2: (1) Simplex ST Male

• Cable Length: 7m (23ft)

• Fiber Count: Simplex

• Insertion Loss: ≤ 0.3dB

• Return Loss: ≥ 50dB

• Bend Radius: 50 mm

• Cable Diameter: 2.0mm

• Cable Jacket: PVC

• Operating Temperature: -20~70°C

• Storage Temperature: -40~80°C

Buy Now