

Cisco QDD-400G-DR4-S Datasheet



Cisco QDD-400G-DR4-S 400G QSFP-DD Transceiver, 400GBASE-DR4, MPO-12, 500m parallel SMF

QDD-400G-DR4-S

The Cisco family of QSFP-DD modules provide the industry's highest bandwidth density while leveraging the backward compatibility to lower-speed QSFP pluggable modules and cables.

The Cisco 400GBASE Quad Small Form-Factor Pluggable Double Density (QSFP-DD) portfolio offers customers a wide variety of super high-density transceiver modules and the flexibility of 400 Gigabit Ethernet connectivity options for data center, high-performance computing networks, enterprise core and distribution layers, and service provider applications. The QSFP-DD modules are our new generation of 400G transceiver modules based on a QSFP-DD form factor.

Features and benefits of Cisco QSFP-DD modules

- Hot-swappable - Input/output device that plugs into 400G Ethernet Cisco QSFP port
- Interoperable - Interoperable with other IEEE-compliant 400GBASE interfaces where applicable
- Certified on Cisco platform - Certified and tested on Cisco QSFP-DD 400G ports for superior performance, quality, and reliability
- Compatible with IEEE 802.3 - High-speed electrical compliant to IEEE 802.3cd and IEEE 802.3bs
- Compatible with MSA - Optical and coding compliant to QSFP-DD MSA Rev4.1, OIF 56G PAM4, and 100G Lambda-

FR4 MSA

- Backward compatibility - QSFP-DD port is backward compatible with QSFP+ and QSFP28 modules

QDD-400G-DR4-S

The Cisco QDD-400G-DR4-S Module supports link lengths of up to 500m parallel SMF with MPO-12 connector. It is compliant to IEEE 802.3bs protocol and 400GAUI-8/CEI-56G-VSR-PAM4 standards. The 400 Gigabit Ethernet signal is carried over four parallel lanes by one wavelength per lane. It can be used as 4x100G breakout to QSFP28-100G-FR-S. FEC is performed on the host platform.

Specifications

- Part ID: QDD-400G-DR4-S
- Product description: Cisco 400G QSFP-DD Transceiver, 400GBASE-DR4, MPO-12, 500m parallel SMF
- Nominal wavelength: 1310nm
- Cable type: Ribbon SMF
- Cable distance: 500m
- Average Transmit Power per lane (dBm) min: -2.9
- Average Transmit Power per lane (dBm) max: 4
- Average Receive Power per lane (dBm) min: -5.9
- Average Receive Power per lane (dBm) max: 4
- Maximum Supported Insertion Loss (IL) (dB): 3
- Nominal rate: 425Gbs
- High-speed electrical: 400GAUI-8/CEI-56G-VSR-PAM4
- Max power consumption (W): 12W
- Pull tab color: Orange
- Operation temperature: 0 to 75°C
- Storage temperature: -40 to 85°C

Platform support

Cisco QDD-400G-DR4-S is supported on a wide range of Cisco equipment.

- Cisco Nexus 9316D-GX
- Cisco N3432D-S

[Buy Now](#)