

Cisco QSFP-100G-DR-S Datasheet



Cisco QSFP-100G-DR-S 100GBASE-DR1 QSFP Transceiver, 500m over SMF

QSFP-100G-DR-S

The Cisco 100GBASE Quad Small Form-Factor Pluggable (QSFP) portfolio offers customers a wide variety of high-density and low-power 100 Gigabit Ethernet connectivity options for data center, high-performance computing networks, enterprise core and distribution layers, and service provider applications. The QSFP-100G modules are our latest generation of 100G transceiver modules solution based on a QSFP form factor.

Features and benefits of Cisco QSFP modules

- Hot-swappable input/output device that plugs into a 100G Gigabit Ethernet Cisco QSFP port
- Interoperable with other IEEE-compliant 100GBASE interfaces where applicable
- Certified and tested on Cisco QSFP-100G ports for superior performance, quality, and reliability
- High-speed electrical interface compliant to IEEE 802.3bm

Cisco QSFP-100G-DR-S

The Cisco QSFP-100G-DR-S Module supports link lengths of up to 500 m over a standard pair of G.652 Single-Mode Fiber (SMF) with duplex LC connectors. The 100 Gigabit Ethernet signal is carried over a single wavelength using

onboard PAM4 modulation and FEC. QSFP-100G-DR-S interoperates with 400G transceivers that comply with IEEE 400GBASE-DR4, such as Cisco's QSFP-400G-DR4-S, via fiber break-out cables.

Specifications

- Product Number: QSFP-100G-DR-S
- Description: Cisco 100GBASE-DR1 QSFP Transceiver, 500m over SMF
- Connector Type: LC
- Wavelength: 1310nm
- Cable Type: SMF
- Cable Distance: 500m
- Power Consumption: 4.3W
- Pull Tab Color: Orange
- Transmit Power (dBm) per lane:
 - Maximum: 4
 - Minimum: -2.9
- Receive Power (dBm) per lane:
 - Maximum: 4
 - Minimum: -5.9
- Transmit and Receive Wavelength (nm): 1304.5 to 1317.5

Dimensions

- Maximum outer dimensions for the QSFP connector module are (H x W x D) 13.5 x 18.4 x 72.4 mm.
- Cisco QSFP connector modules typically weigh 100 grams or less.

Environmental conditions

- Operating temperature range: Commercial temperature range: 0 to 70°C (32 to 158°F)
- Storage temperature range: -40 to 85°C (-40 to 185°F)

Platform support

Cisco QSFP-100G-DR-S is supported on a wide range of Cisco equipment.

- Cisco Nexus 9300-EX Series 93180YC-EX
- Cisco Nexus N9K-C92160YC-X
- Cisco NCS-5501

[Buy Now](#)