

# Cisco QSFP-100G-LR4-I Datasheet



Cisco QSFP-100G-LR4-I 100GBASE-LR4 QSFP I-Temp Transceiver, LC, 10km over SMF

## QSFP-100G-LR4-I

The Cisco 100GBASE Quad Small Form-Factor Pluggable (QSFP) portfolio offers customers a wide variety of high-density and low-power 100 Gigabit Ethernet connectivity options for data center, high-performance computing networks, enterprise core and distribution layers, and service provider applications. The QSFP-100G modules are our latest generation of 100G transceiver modules solution based on a QSFP form factor.

## Features and benefits of Cisco QSFP modules

- Hot-swappable input/output device that plugs into a 100G Gigabit Ethernet Cisco QSFP port
- Interoperable with other IEEE-compliant 100GBASE interfaces where applicable
- Certified and tested on Cisco QSFP-100G ports for superior performance, quality, and reliability
- High-speed electrical interface compliant to IEEE 802.3bm

## Cisco QSFP-100G-LR4-I

The Cisco QSFP100 LR4 industrial temperature Module supports link lengths of up to 10km over a standard pair of G.652 single-mode fiber with duplex LC connectors. It complies with the IEEE 100GBASE-LR4 specification, which does

not employ the use of FEC. QSFP-100G-LR4-I supports 100GBase Ethernet rate within an industrial temperature range.

## Specifications

- Product Number: QSFP-100G-LR4-I
- Description: Cisco 100GBASE-LR4 QSFP I-Temp Transceiver, LC, 10km over SMF
- Connector Type: LC
- Wavelength: 1295, 1300, 1304, 1309nm
- Cable Type: SMF
- Cable Distance: 10km
- Power Consumption: 4.0W
- Pull Tab Color: Blue
- Transmit Power (dBm) per lane:
  - Maximum: +4.5
  - Minimum: -4.3
- Receive Power (dBm) per lane:
  - Maximum: +4.5
  - Minimum: -10.6
- Transmit and Receive Wavelength (nm): Four lanes: 1295, 1300, 1304, 1309

## Dimensions

- Maximum outer dimensions for the QSFP connector module are (H x W x D) 13.5 x 18.4 x 72.4 mm.
- Cisco QSFP connector modules typically weigh 100 grams or less.

## Environmental conditions

- Operating temperature range: Industrial temperature range: -40 to 85°C (-40 to 185°F)

- Storage temperature range: -40 to 85°C (-40 to 185°F)

## Platform support

Cisco QSFP-100G-LR4-I is supported on a wide range of Cisco equipment.

- Cisco NCS-5508
- Cisco ONS Transport Platform NCS-1002-K9
- Cisco Nexus N9K-C92160YC-X
- Cisco Nexus 9000 Series (Modular 9500) N9K-X9432C-S
- Cisco NCS-5501
- Cisco Nexus 9000 Series (Fixed 9200) N9K-C92160YC-X
- Cisco Nexus 9300-EX Series 93180YC-EX
- Cisco Nexus 3000 Series N3K-C3232C
- Cisco Catalyst C9500-24Y4C

[Buy Now](#)