

H3C QSFP-100G-SWDM4-MM850 Datasheet



H3C QSFP-100G-SWDM4-MM850 100Gbps 100m SWDM4 850nm MM QSFP28 Transceiver Module

QSFP-100G-SWDM4-MM850

H3C QSFP-100G-SWDM4-MM850 100Gbps 100m SWDM4 850nm MM QSFP28 Transceiver Module

The H3C QSFP-100G-SWDM4-MM850 100G QSFP28 SWDM4 optical transceiver module is designed for 100-Gigabit Ethernet links up to 100m over a multimode. It complies with QSFP28 MSA, IEEE802.3cm-2020, and CAUI-4 (no FEC)1. The module contains 4 channels of 25Gbps VCSEL and PIN photodetectors, transmitting and receiving over a simplex LC fiber using SWDM4 optics.

Specifications

- Brand: H3C
- Part Numbers: QSFP-100G-SWDM4-MM850, H9152RGPL-H3C
- Form Factor: QSFP28
- Max Data Rate: 103.1Gb/s
- Wavelength: 850nm, 880nm, 910nm, 940nm
- Max Distance: 100m
- Connector: Duplex LC
- Transmitter Type: 850nm VCSEL
- Cable Type: MMF
- Receiver Type: PIN
- TX Power: -7.1~+4.2dBm
- Receiver Sensitivity: <-9.4dBm
- Protocols: 100G Ethernet, QSFP28 MSA Compliant

- Operation Temperature: 0 to 70°C (32 to 158°F)

[Buy Now](#)