

# H3C QSFP-100G-eSR4-MM850 Datasheet



H3C QSFP-100G-eSR4-MM850 100GBASE-SR4 QSFP28 850nm 300m DOM MTP/MPO-12 MMF Optical Transceiver Module AFBR-89CDDZ-H3C

QSFP-100G-eSR4-MM850

H3C QSFP-100G-eSR4-MM850 100GBASE-SR4 QSFP28 850nm 300m DOM MTP/MPO-12 MMF Optical Transceiver Module AFBR-89CDDZ-H3C

The H3C QSFP-100G-eSR4-MM850 100G QSFP28 SR4 transceiver modules are designed for 100G Ethernet links over multimode fiber. They are compliant with IEEE 802.3bm 100GBASE-SR4 and CAUI-4. Digital diagnostic functions are available through the QSFP28 MSA-specified I2C interface.

## Specifications

- Brand: H3C
- Part Numbers: □□QSFP-100G-eSR4-MM850, AFBR-89CDDZ-H3C
- Form Factor: QSFP28
- Max Data Rate: 103.1Gbps
- Wavelength: 850nm
- Max Distance: 100m on OM4
- Connector: MTP/MPO-12
- Transmitter Type: 850nm VCSEL
- Cable Type: MMF
- Receiver Type: PIN
- TX Power: -8.4~+2.4dBm
- Receiver Sensitivity: < -10.3dBm
- Protocols: 100G Ethernet, MSA Compliant

- Operation Temperature: 0 to 70°C (32 to 158°F)

[Buy Now](#)