

# Cisco QSFP-40G-CSR4 Datasheet



Cisco QSFP-40G-CSR4 40GBASE-CSR4 QSFP Module for MMF

QSFP-40G-CSR4

The Cisco 40GBASE QSFP (Quad Small Form-Factor Pluggable) portfolio offers customers a wide variety of high-density and low-power 40 Gigabit Ethernet connectivity options for data center, high-performance computing networks, enterprise core and distribution layers, and service provider applications.

Features and benefits of Cisco QSFP modules

- Hot-swappable input/output device that plugs into a 40 Gigabit Ethernet Cisco QSFP port
- Interoperable with other IEEE-compliant 40GBASE interfaces where applicable
- Certified and tested on Cisco QSFP 40G ports for superior performance, quality, and reliability
- High-speed electrical interface compliant to the IEEE 802.3ba standard
- QSFP Form factor, 2-wire I2C communication interface and other low-speed electrical interface compliant to SFF 8436 and QSFP Multisource Agreement (MSA)

Cisco QSFP-40G-CSR4

Cisco 40GBASE-CSR4 QSFP Modules extend the reach of the IEEE 40GBASE-SR4 interface to 300 and 400 meters on laser-

optimized OM3, and OM4/OM5 multimode parallel fiber, respectively. Each 10-gigabit lane of this module is compliant to IEEE 10GBASE-SR specifications. This module can be used for native 40G optical links over 12-fiber parallel cables with MPO/MTP female connectors or in a 4x10G breakout mode with parallel to duplex fiber breakout cables for connectivity to four 10GBASE-SR interfaces. Cisco QSFP-40G-CSR4 is optimized to guarantee interoperability over the complete specification range of 10GBASE-SR.

## Specifications

- Product number: QSFP-40G-CSR4
- Description: Cisco 40GBASE-CSR4 QSFP Module for MMF
- Product Type: 40GBASE-CSR4, 4 lanes, 850 nm MMF
- Connector Type: MPO-12
- Wavelength: 850nm
- Cable type: MMF
- Cable distance:
  - 82m @ OM2
  - 300m @ OM3
  
  - 400m @ OM4/OM5
- Power consumption: 1.5W
- Pull tab color: Orange
- Transmit power (dBm)
  - Maximum: 0, per lane
  - Minimum: -7.3, per lane
- Receive power (dBm)
  - Maximum: 0, per lane
  - Minimum: -9.9, per lane
- Transmit and receive wavelength (nm): 840 to 860
- Operating temperature range: Commercial temperature range: 0 to 70°C (32 to 158°F)
- Storage temperature range: -40 to 85°C (-40 to 185°F)

## Platform support

Cisco QSFP-40G-CSR4 is supported on a wide range of Cisco equipment.

- Cisco Nexus 9396PX
- Cisco Nexus 5000 N5K-C56128P
- Cisco Nexus 9000 N9K-C9372TX
- Cisco Nexus 3000 N3K-C3064X
- Cisco Nexus 3000 N3K-C3132Q-X
- Cisco Nexus 3000 N3K-C3064T
- Cisco Nexus 9000 N9K-C9272Q
- Cisco Nexus 3000 N3K-C31128PQ-10GE
- Cisco Nexus 9000 N9K-X9464TX
- Cisco Nexus 9000 N9K-C9372PX
- Cisco 3850WS-C3850-48XS-E
- Cisco Nexus 3000 N3K-C3064PQ-10GE
- CISCO Nexus 93180LC-EX
- Cisco Nexus 7000 N77-F324FQ-25
- Cisco Nexus 9000 N9K-X9432PQ
- Cisco NCS-5501
- Cisco Nexus 7000 N7K-M206FQ-23L
- Cisco Nexus 9000 N9K-C9372TX-E
- Cisco Nexus 9000 N9K-M6PQ-E
- Cisco Nexus 6000 N6K-C6001-64T
- Cisco Nexus 5000 N5K-C5672UP
- Cisco Nexus 3000 N3K-C3232C
- Cisco A9K-MPA-2X40GE
- Cisco Nexus 6000 N6004-96Q
- CISCO Nexus 9336C-FX2
- Cisco Nexus 2000 N2K- 2332TQ
- Cisco Nexus 9000 N9K-M6PQ-E
- Cisco Nexus 9000 N9K-X9736PQ

- Cisco Nexus 9000 N9K-C9372PX-E
- Cisco Nexus 9000 N9K-C9372PX
- Cisco Nexus 9300-EX Series 93180YC-EX
- Cisco Nexus 3000 N3K-3172PQ
- Cisco 3850 WS-C3850-48XS-S
- Cisco Nexus 9000 N9K-C93120TX
- Cisco Nexus 9000 N9K-C9332PQ
- Cisco Nexus 9000 N9K-X9564PX (uplinks)
- Cisco Nexus 9000 N9K-C92160YC-X
- Cisco Nexus 2000 N2K-C2248PQ
- Cisco Nexus 9000 N9K-M12PQ
- Cisco Nexus 6000 N6K-C6004-M12Q
- Cisco Nexus 3000 N3K-3172TQ
- Cisco Nexus 3000 N3K-C3164Q
- Cisco Nexus 9000 N9K-M6PQ
- Cisco Nexus 9000 N9K-X9636PQ
- Cisco Nexus 9000 N9K-C9336PQ
- Cisco Catalyst C9500-24Y4C
- Cisco Nexus 3000 N3K-C3064-32T
- Cisco Nexus 7000 N7K-F312FQ-25
- Cisco Nexus 3000 N3K-C3264Q
- Cisco Nexus 6000 N6004-B-24Q
- Cisco C6800-SUP6T-XL
- Cisco Nexus 9000 N9K-X9464PX
- Cisco Nexus 9000 N9K-X9564TX (uplinks)
- Cisco Nexus 2000 N2K-2348TQ
- Cisco C6800-SUP6T
- Cisco C3850-NM-2-40G
- Cisco Nexus 9000 N9K-C93120TX
- Cisco Nexus 6000 N6K-C6001-64P
- Cisco Nexus 92304QC
- Cisco 6800 C6824-X-LE-40G
- Cisco Nexus 2000 N2K-2348UPQ
- Cisco Nexus 9000 N9K-M6PQ-E
- Cisco WS-C3850-48XS-F-S
- Cisco Nexus 5000 N55-M4Q
- Cisco Nexus 9000 N9K-C9372PX-E

- Cisco Nexus 5000 N5K-C5672UP
- Cisco Nexus 9000 N9K-C9332PQ
- Cisco ASR 9000 A9K-MPA-1X40GE
- Cisco Nexus 9000 N9K-M6PQ
- Cisco Nexus 9000 N9K-C9372TX-E
- Cisco Nexus 9000 N9K-C9372TX-E
- Cisco Nexus 9000 N9K-X9432C-S
- Cisco 6500 C6800-SUP6T
- Cisco 6800 C6840-X-LE-40G
- Cisco Nexus 9000 N9K-M12PQ
- Cisco Nexus 3000 N3K-3132Q
- Cisco Nexus 9000 N9K-X9536PQ

[Buy Now](#)