

# Cisco QSFP-40G-LR4 Datasheet



Cisco QSFP-40G-LR4 40GBASE-LR4 QSFP Module for SMF with OTU-3 data-rate support

## QSFP-40G-LR4

The Cisco 40GBASE QSFP (Quad Small Form-Factor Pluggable) portfolio offers customers a wide variety of high-density and low-power 40 Gigabit Ethernet connectivity options for data center, high-performance computing networks, enterprise core and distribution layers, and service provider applications.

## Features and benefits of Cisco QSFP modules

- Hot-swappable input/output device that plugs into a 40 Gigabit Ethernet Cisco QSFP port
- Interoperable with other IEEE-compliant 40GBASE interfaces where applicable
- Certified and tested on Cisco QSFP 40G ports for superior performance, quality, and reliability
- High-speed electrical interface compliant to the IEEE 802.3ba standard
- QSFP Form factor, 2-wire I2C communication interface and other low-speed electrical interface compliant to SFF 8436 and QSFP Multisource Agreement (MSA)

## Cisco QSFP-40G-LR4

The Cisco 40GBASE-LR4 QSFP module supports link lengths of up to 10 kilometers over a standard pair of G.652 single-

mode fiber with duplex LC connectors. The 40 Gigabit Ethernet signal is carried over four wavelengths. Multiplexing and demultiplexing of the four wavelengths are managed within the device.

## Specifications

- Product number: QSFP-40G-LR4
- Description: Cisco 40GBASE-LR4 QSFP Module for SMF with OTU-3 data-rate support
- Product Type: 40GBASE-LR4, 1310 nm, SMF with OTU3 data-rate support
- Connector Type: LC
- Wavelength: 1310nm
- Cable type: SMF
- Cable distance: 10km
- Power consumption: 3.5W
- Pull tab color: Blue
- Transmit power (dBm)
  - Maximum: 2.3, per lane
  - Minimum: -7, per lane
- Receive power (dBm)
  - Maximum: 2.3, per lane
  - Minimum: -13.7, per lane
- Transmit and receive wavelength (nm): Four lanes: 1271, 1291, 1311, 1331
- Operating temperature range: Commercial temperature range: 0 to 70°C (32 to 158°F)
- Storage temperature range: -40 to 85°C (-40 to 185°F)

## Platform support

Cisco QSFP-40G-LR4 is supported on a wide range of Cisco equipment.

- Cisco Nexus 9396PX
- Cisco NCS-5501
- Cisco Nexus 9300-EX Series 93180YC-EX
- Cisco Catalyst C9500-24Y4C
- Cisco Nexus 92304QC
- Cisco Nexus 3000 N3K-C3064T
- Cisco Nexus 9000 N9K-X9736PQ
- Cisco Nexus 9000 N9K-C9372TX-E
- Cisco Nexus 9000 N9K-C93120TX
- Cisco Nexus 5000 N5K-C5672UP
- Cisco Nexus 6000 N6004-96Q
- Cisco Nexus 9000 N9K-C9372PX-E
- Cisco Nexus 3000 N3K-3132Q
- Cisco Nexus 9000 N9K-M6PQ-E
- Cisco Nexus 9000 N9K-X9464TX
- Cisco Nexus 6000 N6K-C6001-64T
- Cisco Nexus 9000 N9K-C9332PQ
- Cisco Nexus 9000 N9K-X9564PX (uplinks)
- Cisco Nexus 9000 N9K-C9332PQ
- Cisco Nexus 3000 N3K-3172TQ
- Cisco Nexus 5000 N5K-C5672UP
- Cisco Nexus 9000 N9K-C9372TX-E
- Cisco Nexus 2000 N2K-2348UPQ
- Cisco Nexus 9000 N9K-X9564TX (uplinks)
- Cisco Nexus 3000 N3K-C3016Q
- Cisco Nexus 9000 N9K-C9336PQ
- Cisco Nexus 3000 N3K-C3064X
- Cisco Nexus 9000 N9K-X9536PQ
- Cisco Nexus 9000 N9K-X9464PX
- Cisco Nexus 9000 N9K-C93120TX
- Cisco Nexus 9000 N9K-C9372PX
- Cisco Nexus 3000 N3K-C3164Q
- Cisco Nexus 9000 N9K-C9372PX
- Cisco Nexus 9000 N9K-X9636PQ
- Cisco Nexus 9000 N9K-X9432C-S

- Cisco Nexus 9000 N9K-C9372TX
- Cisco Nexus 3000 N3K-3172PQ
- Cisco Nexus 3000 N3K-C31128PQ-10GE
- Cisco Nexus 7000 N7K-M206FQ-23L
- Cisco Nexus 9000 N9K-M12PQ
- Cisco Nexus 5000 N5K-C56128P
- Cisco Nexus 9000 N9K-C9372PX-E
- Cisco Nexus 3000 N3K-C3132Q-X
- Cisco Nexus 2000 N2K- 2332TQ
- Cisco Nexus 9000 N9K-C92160YC-X
- Cisco Nexus 9000 N9K-M6PQ
- Cisco Nexus 6000 N6K-C6004-M12Q
- Cisco Nexus 5000 N55-M4Q
- Cisco Nexus 7000 N77-F324FQ-25
- Cisco Nexus 9000 N9K-M6PQ-E
- Cisco Nexus 2000 N2K-2348TQ
- Cisco Nexus 9000 N9K-M6PQ-E
- Cisco Nexus 3000 N3K-C3064PQ
- Cisco Nexus 3000 N3K-C3064PQ-10GE
- Cisco Nexus 9000 N9K-C9272Q
- Cisco Nexus 2000 N2K-C2248PQ
- Cisco Nexus 3000 N3K-C3064-32T
- Cisco Nexus 9000 N9K-M12PQ
- Cisco Nexus 6000 N6004-B-24Q
- Cisco Nexus 9000 N9K-M6PQ
- Cisco Nexus 7000 N7K-F312FQ-25
- Cisco Nexus 6000 N6K-C6001-64P
- Cisco Nexus 9000 N9K-X9432PQ

[Buy Now](#)