

Cisco QSFP-40G-SR4-S Datasheet



Cisco QSFP-40G-SR4-S 40GBASE-SR4 QSFP Module for MMF

QSFP-40G-SR4-S

The Cisco 40GBASE QSFP (Quad Small Form-Factor Pluggable) portfolio offers customers a wide variety of high-density and low-power 40 Gigabit Ethernet connectivity options for data center, high-performance computing networks, enterprise core and distribution layers, and service provider applications.

Features and benefits of Cisco QSFP modules

- Hot-swappable input/output device that plugs into a 40 Gigabit Ethernet Cisco QSFP port
- Interoperable with other IEEE-compliant 40GBASE interfaces where applicable
- Certified and tested on Cisco QSFP 40G ports for superior performance, quality, and reliability
- High-speed electrical interface compliant to the IEEE 802.3ba standard
- QSFP Form factor, 2-wire I2C communication interface and other low-speed electrical interface compliant to SFF 8436 and QSFP Multisource Agreement (MSA)

Cisco QSFP-40G-SR4-S (S-Class)

The S-Class Cisco 40GBASE-SR4-S QSFP module supports link lengths of 100 and 150 meters, respectively, on laser-

optimized OM3, and OM4/OM5 multimode fibers. QSFP-40G-SR4-S is aligned to IEEE 40GBASE-SR4 optical specifications which support high-bandwidth 40G optical links over 12-fiber parallel fiber terminated with MPO/MTP multifiber female connectors. Because the QSFP-40G-SR4-S does not support 4x10G breakout connectivity, see QSFP-40G-SR4 or QSFP-40G-CSR4 for such applications. QSFP-40G-SR4-S does not support FCoE.

Specifications

- Product number: QSFP-40G-SR4-S
- Description: Cisco 40GBASE-SR4 QSFP Module for MMF
- Product Type: 40GBASE-SR4, 4 lanes, 850 nm MMF
- Connector Type: MPO-12
- Wavelength: 850nm
- Cable type: MMF
- Cable distance:
 - 100m @ OM3
 - 150m @ OM4/OM5
- Power consumption: 1.5W
- Pull tab color: Beige
- Transmit power (dBm)
 - Maximum: 2.4, per lane
 - Minimum: -7.6, per lane
- Receive power (dBm)
 - Maximum: 2.4, per lane
 - Minimum: -9.5, per lane
- Transmit and receive wavelength (nm): 840 to 860
- Operating temperature range: Commercial temperature range: 0 to 70°C (32 to 158°F)
- Storage temperature range: -40 to 85°C (-40 to 185°F)

Platform support

Cisco QSFP-40G-SR4-S is supported on a wide range of Cisco equipment.

- Cisco Nexus 9396PX
- Cisco Catalyst C9500-24Y4C
- Cisco Nexus 6000 N6K-C6004-M12Q
- Cisco Nexus 5000 N55-M4Q
- Cisco Nexus 6000 N6K-C6001-64T
- Cisco Nexus 9000 N9K-M12PQ
- Cisco Nexus 9000 N9K-C9336PQ
- Cisco Nexus 7000 N7K-M206FQ-23L
- Cisco Nexus 9000 N9K-X9464PX
- Cisco Nexus 9000 N9K-C93120TX
- Cisco Nexus 3000 N3K-3172TQ
- Cisco Nexus 9000 N9K-C9332PQ
- Cisco Nexus 9000 N9K-M12PQ
- Cisco Nexus 9000 N9K-X9536PQ
- Cisco Nexus 9000 N9K-C92160YC-X
- Cisco Nexus 5000 N55-M4Q
- Cisco Nexus 9000 N9K-M6PQ
- Cisco Nexus 6000 N6004-96Q
- Cisco Nexus 9000 N9K-C9372PX
- Cisco Nexus 3000 N3K-3172PQ
- Cisco Nexus 3000 N3K-C3132Q-X
- Cisco Nexus 9000 N9K-C9372PX-E
- Cisco Nexus 9000 N9K-C9372PX
- Cisco Nexus 3000 N3K-C3064PQ-10GE
- Cisco Nexus 9000 N9K-C9272Q
- Cisco Nexus 9000 N9K-M6PQ
- Cisco Nexus 9000 N9K-X9432C-S
- Cisco Nexus 9000 N9K-C9372TX
- Cisco Nexus 3000 N3K-C3016Q
- Cisco Nexus 5000 N5K-C56128P
- Cisco Nexus 3000 N3K-C3064X
- Cisco Nexus 9000 N9K-M6PQ-E
- Cisco Nexus 9000 N9K-X9736PQ
- Cisco Nexus 9000 N9K-C93120TX
- Cisco Nexus 9000 N9K-X9564PX (uplinks)
- Cisco Nexus 9000 N9K-C9372TX-E
- Cisco ASR 9000 A9K-MPA-1X40GE

- Cisco Nexus 9000 N9K-C9372TX-E
- Cisco Nexus 9000 N9K-X9636PQ
- Cisco Nexus 2000 N2K-2348UPQ
- Cisco Nexus 9000 N9K-X9432PQ
- Cisco Nexus 7000 N77-F324FQ-25
- Cisco A9K-MPA-2X40GE
- Cisco Nexus 9000 N9K-M6PQ-E
- Cisco NCS-5501
- Cisco Nexus 92304QC
- Cisco Nexus 2000 N2K- 2332TQ
- Cisco Nexus 9000 N9K-X9464TX
- Cisco Nexus 6000 N6004-B-24Q
- Cisco Nexus 7000 N7K-M202CF-22L
- Cisco Nexus 3000 N3K-C3064-32T
- Cisco Nexus 2000 N2K-2348TQ
- Cisco Nexus 3000 N3K-3172PQ
- Cisco Nexus 9000 N9K-M6PQ-E
- Cisco Nexus 3000 N3K-C31128PQ-10GE
- Cisco Nexus 9300-EX Series 93180YC-EX
- Cisco Nexus 2000 N2K-C2248PQ
- Cisco Nexus 5000 N5K-C5672UP
- Cisco Nexus 9000 N9K-C9372PX-E
- Cisco Nexus 9000 N9K-C9332PQ
- Cisco Nexus 3000 N3K-C3064PQ
- Cisco Nexus 5000 N5K-C5672UP
- Cisco Nexus 3000 N3K-C3064T
- Cisco Nexus 6000 N6K-C6001-64P
- Cisco Nexus 9000 N9K-X9564TX (uplinks)

[Buy Now](#)