

# Moxa SFP-1G20ALC Datasheet



Moxa SFP-1G20ALC WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature

## SFP-1G20ALC

Moxa's small form-factor pluggable transceiver (SFP) Ethernet fiber modules for Gigabit Ethernet provide coverage across a wide range of communication distances.

## Specifications

- Part Number: SFP-1G20ALC
- Product Type: SFP-1G Series
- Product: WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
- Ethernet Interface
  - Ports: 1
  - Connectors: Simplex LC connector
  - Transceiver Type: Single-mode
  - Fiber Cable Type: G.652
  - Typical Distance: 20km
  - Wavelength
    - Typical (nm): TX 1310, RX 1550
    - TX Range (nm): 1270 to 1355
    - RX Range (nm): 1480 to 1580

- Optical Power
  - TX Range (dBm): -2 to -8
  - RX Range (dBm): -2 to -23
- Link Budget (dB): 15
- Dispersion Penalty (dB): 3
- Power Parameters
  - Power Consumption: Max. 1 W
- Environmental Limits
  - Operating Temperature: 0 to 60°C (32 to 176°F)
  - Storage Temperature (package included): -40 to 85°C (-40 to 185°F)
  - Ambient Relative Humidity: 5 to 95% (non-condensing)
- Standards and Certifications
  - Safety: CE, FCC, TUV (EN 60825), UL 60950-1
  - Maritime: DNV-GL

For more information of this Moxa SFP-1G20ALC, please visit Moxa website:

<https://www.moxa.com/en/products/accessories/sfp-modules/gigabit-ethernet-sfp-modules/sfp-1g-series/sfp-1g20alc>

[Buy Now](#)