

Moxa SFP-1G20BLC Datasheet



Moxa SFP-1G20BLC WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature

SFP-1G20BLC

Moxa's small form-factor pluggable transceiver (SFP) Ethernet fiber modules for Gigabit Ethernet provide coverage across a wide range of communication distances.

Specifications

- Part Number: SFP-1G20BLC
- Product Type: SFP-1G Series
- Product: WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
- Ethernet Interface
 - Ports: 1
 - Connectors: Simplex LC connector
 - Transceiver Type: Single-mode
 - Fiber Cable Type: G.652
 - Typical Distance: 20km
 - Wavelength
 - Typical (nm): TX 1550, RX 1310
 - TX Range (nm): 1530 to 1570
 - RX Range (nm): 1260 to 1360

- Optical Power
 - TX Range (dBm): -2 to -8
 - RX Range (dBm): -2 to -23
- Link Budget (dB): 15
- Dispersion Penalty (dB): 3
- Power Parameters
 - Power Consumption: Max. 1 W
- Environmental Limits
 - Operating Temperature: 0 to 60°C (32 to 176°F)
 - Storage Temperature (package included): -40 to 85°C (-40 to 185°F)
 - Ambient Relative Humidity: 5 to 95% (non-condensing)
- Standards and Certifications
 - Safety: CE, FCC, TUV (EN 60825), UL 60950-1
 - Maritime: DNV-GL

For more information of this Moxa SFP-1G20BLC, please visit Moxa website:

<https://www.moxa.com/en/products/accessories/sfp-modules/gigabit-ethernet-sfp-modules/sfp-1g-series/sfp-1g20blc>

[Buy Now](#)