

# TP-Link SM311LM Datasheet



TP-Link SM311LM 1000-Base-SX MMF Mini GBIC Module

SM311LM

TP-Link SM311LM 1000-Base-SX MMF Mini GBIC Module

The SM311LM (TL-SM311LM) Fiber Module Cards are introduced for extending transfer distance. Attached to our managed/smart switches, they can extend the distance to several kilometers even tens of kilometers which can basically satisfy the distance requirement of LAN. Users can choose whether and which items to use the fiber modules according to the demand in order to lower cost.

## Features

- Multi-mode MiniGBIC module
- Compatible with T3700 series, T2700 series, T2600 series, T2500 series, T1700 series, T1600 series, T1500 series, 2/3/5 series switches and MC220L

## Specifications

- Standards and Protocols: IEEE 802.3z, CSMA/CD, TCP/IP
- Wave Length: 850nm
- Dimensions (W\*D\*H): 2.2\*0.5\*0.5 in (55.4\*13.7\*12.9 mm)
- Power Supply: 3.3V
- Safety & Emission: FCC, CE
- Cabel: Multi-mode Fiber

- Fiber Type: 50/125µm or 62.5/125µm Multi-mode
- Max. Cable Length: 550m
- Data Rate: 1.25Gbps
- Port Type: LC/UPC
- Hardware Features:
  - DDM
  - SFP-MSA
  - Hot Swappable
- Environment:
  - Operating Temperature: 0°C~70°C (32°F~158°F)
  
  - Storage Temperature: -40°C~80°C (-40°F~176°F)
  - Operating Humidity: 10%~90% non-condensing
  - Storage Humidity: 5%~90% non-condensing

[Buy Now](#)